

#### **DEC1850FI**



#### **FEATURES**

ClearSight™ LED lighting system fully illuminates the interior and reduces shadows

Sleek stainless accents trim the interior, matching the sophistication of the exterior

Easily customize settings with the tap of a finger via the conveniently accessible touch control panel

Night Mode optimizes the interior lighting based on the detected ambient light, reducing the brightness by 90% in dim environments

Position adjustable door shelves at various heights to accommodate assorted items

Fresh-tasting, filtered ice ready on demand; activate Max Ice Mode to temporarily increase ice production

Locks in cold air with a magnetic door seal system

Wi-Fi enabled for convenient remote access using the Sub-Zero Group Owner's App

Sub-Zero offers an industry-leading full two-year warranty on appliances, along with a full five-year sealed system warranty

Accepts custom panels for an integrated look within cabinetry or stainless-steel accessory panels and handles to match other Sub-Zero, Wolf, and Cove products\*

#### **ACCESSORIES**

Reduced Toekick Divider

Stainless Steel Side Panel

Water Filter

**Dual Installation Kits** 

Stainless Steel Dual Installation Kickplates

Stainless Steel Door Panels With Pro Handle

Stainless Steel Door Panels With Tubular Handle

Stainless Steel Pro and Tubular Handles

Accessories are available through an authorized dealer. For local dealer information, visit <a href="mailto:subzero-wolf.com/locator">subzero-wolf.com/locator</a>.



#### HANDLE ACCESSORIES



# **PRODUCT DETAILS**

#### **FREEZER**

- · LED freezer lights
- · 4 freezer shelves (3 adjustable; 1 stationary)
- · 2 storage drawers with adjustable dividers
- · 5 adjustable door bins
- · Ice drawer with automatic ice maker





### **PRODUCT SPECIFICATIONS**

Model	DEC1850FI
Dimensions	18"W x 84"H x 24"D
Freezer Capacity	8.8 cu. ft.
Weight	285 lbs
Electrical Supply	115 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Plumbing Supply	1/4" OD copper, braided stainless steel or PEX tubing
Plumbing Pressure	35–120 psi

### **ELECTRICAL**

#### **PLUMBING**






 $\ensuremath{\mathsf{NOTE}}.$  The electrical outlet must be positioned with the grounding prong to the right of the thinner blades.

**PANEL SPECIFICATIONS** For complete panels specifications including width/height, weight requirements and thickness requirements visit <a href="mailto:subzero-wolf.com/reveal">subzero-wolf.com/reveal</a>.


NOTE: Dimensions in parenthesis are in millimeters unless otherwise specified


### **INTERIOR VIEW**




This illustration is intended for interior reference only and may not represent the exterior of the model being specified.

# **DIMENSIONS**





# **STANDARD INSTALLATION**



NOTE:3<sup>1</sup>/<sub>2</sub>" (89) finished returns will be visible and should be finished to match cabinetry

