MOLF

DF606F



FEATURES

Cook at higher highs and lower lows with six dual-stacked, sealed burners that produce up to 20,000 Btu and deliver as low as 300 Btu

Slide pots and pans on a French top that allows for true cooking finesse

Clean up sloshes and spills easily with the seamless, sealed, black porcelain-coated burner pans

Assures predictably delicious results with a variety of modes including Convection Roast, Proof, and Dehydrate

Control heat and airflow expertly as dual convection creates just the right cooking environment for everything from Cornish hens to cherry pie to butternut squash

Operate easily with a control panel that rotates out of sight when not in use

Multi-task with an additional 30" oven

Leave nothing to chance. Our temperature probe alerts you when your dish has reached the desired temperature for worry-free, delicious results

Includes options such as self-clean, delayed start, timed cook, Sabbath mode, and more

Re-ignites flame automatically with our spark ignition system for improved temperature control and added safety

Move pots and pans effortlessly across the continuous cast-iron grates

Find your kitchen style with a choice of iconic red, black, or brushed stainless control knobs

See food clearly with bright interior halogen lights and large double-panel glass door windows

ACCESSORIES

- 2-Burner Wok Grate
- 3 1/4" Front Leg Covers
- 3 1/4" Rear Caster Covers
- 3 3/4" (95) Front Leg Covers
- 3 3/4" Rear Caster Covers
- 30" Bake Stone Kit
- 30" Broiler Pan and Rack
- 30" Full-Extension Ball-Bearing Oven Rack
- 4 1/4" Front Leg Covers
- 4 1/4" Rear Caster Covers
- 4 3/4" Front Leg Covers
- 4 3/4" Rear Caster Covers
- 48" and 60" Black Knobs
- 48" and 60" Red Knobs
- 48" and 60" Stainless Steel Knobs

Dehydration Kit

Filler Trim (2-pc)




KNOB OPTIONS







TOP CONFIGURATION



RANGETOP SPECIFICATIONS

- 1 9,200 Btu burner
- 1 20,000 Btu burner
- · Stainless-steel island trim
- 2 15,000 Btu burners
- 2 18,000 Btu burners
- 1 15,000 Btu French top
- · Stainless-steel French top cover

Oven Rack Set (3)
Premier Baking Sheet
Temperature Probe
Brushed stainless, brass or chrome bezels
5" and 10" stainless steel risers, and 20" riser with shelf
Accessories available through an authorized dealer. For local dealer information, visit subzero-wolf.com/locator .


Specifications are subject to change without notice. This information was generated on May 17, 2025. Verify specifications prior to finalizing your cabinetry/enclosures.



PRODUCT SPECIFICATIONS


Model	DF606F
Dimensions	60 1/8"W x 36 7/8"H x 29 1/2"D
Oven 1 Interior Dimensions	25cubic feetW x 16 1/2"H x 19"D
Oven 2 Interior Dimensions	25cubic feetW x 16 1/2"H x 19"D
Oven 1 Usable Capacity	2.8 cu. ft.
Oven 1 Overall Capacity	4.5 cu. ft.
Oven 2 Usable Capacity	2.8 cu. ft.
Oven 2 Overall Capacity	4.5 cu. ft.
Door Clearance	19 1/2"
Electrical Supply	240/208 VAC, 60 Hz
Electrical Service	50 amp dedicated circuit
Gas Supply	3/4" ID line
Gas Inlet	1/2" NPT female

ELECTRICAL GAS




 $\ensuremath{\text{NOTE:}}$ Dimensions in parenthesis are in millimeters unless otherwise specified

DIMENSIONS



STANDARD INSTALLATION



*Without ventilation hood, 36" (914) minimum clearance countertop to combustible materials, 44" (118) for charbroiler.

NOTE: Shaded area above countertop indicates minimum clearance to combustible surfaces, combustible materials cannot be located within this area.

For island installation, 12" (305) minimum clearance back of range to combustible rear wall above countertop.