

**PI663418**

## FEATURES

Rigorously tested for decades of use

Exceptional support from our Customer Care team in Madison

Heavy-duty stainless steel construction

Blower required (internal, in-line or remote blowers available)

Handfinished with hemmed edges and welded seams

Recessed controls for sleeker look

Infinite speed blower control

Heat sentry for safety

Bright halogen lighting

Transition with backdraft minimizes backward flow of cold air

## ACCESSORIES

1100 CFM Inline Blower

12" Duct Cover

1200 CFM Internal Blower

1200 CFM Remote Blower

1500 CFM Remote Blower

18" Duct Cover

24" Duct Cover

30" Duct Cover

300 CFM Internal Blower

36" Duct Cover

400 CFM Internal Blower

6" Duct Cover

600 CFM Inline Blower

600 CFM Internal Blower

600 CFM Remote Blower

800 CFM Internal Blower

900 CFM Remote Blower

Make-Up Air Damper

Accessories available through an authorized dealer.

For local dealer information, visit [subzero-wolf.com/locator](http://subzero-wolf.com/locator).




## BLOWER OPTIONS

- 300 CFM Internal
- 400 CFM Internal
- 600 CFM Internal
- 800 CFM Internal
- 1200 CFM Internal
- 600 CFM Inline
- 1100 CFM Inline
- 600 CFM Remote
- 900 CFM Remote
- 1200 CFM Remote
- 1500 CFM Remote

## PRODUCT SPECIFICATIONS

Model	PI663418
Dimensions	66"W x 18"H x 34"D
Weight	168 lbs
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical
Discharge Dimensions	10" Round
Bottom of Hood to Countertop	30" to 36"

## ELECTRICAL



**NOTE:** Dimensions in parenthesis are in millimeters unless otherwise specified

## DIMENSIONS

