

## PWC362418

### FEATURES

- Heavy-duty stainless steel construction

---

- Handfinished with hemmed edges and welded seams

---

- Blower required (internal, in-line or remote blowers available)

---

- Recessed controls for sleeker look

---

- Infinite speed blower control

---

- Bright halogen lighting

---

- Heat sentry for safety

---

- Transition with backdraft minimizes backward flow of cold air

---

- Install with accessory duct cover for chimney-style hood

---

- Rigorously tested in our U.S. manufacturing facilities for decades of use

---

- Exceptional 24/7 support from our Customer Care team in Madison

### ACCESSORIES

- 1100 CFM Inline Blower

---

- 1200 CFM Internal Blower

---

- 1200 CFM Remote Blower

---

- 1500 CFM Remote Blower

---

- 30" Duct Cover

---

- 36" Duct Cover

---

- Backsplash

---

- Backsplash with Warming Racks

---

- Make-Up Air Damper

---

- 38" high stainless steel backsplash with or without warming racks

---

- Make-up air damper

Accessories available through an authorized dealer.  
For local dealer information, visit [subzero-wolf.com/locator](http://subzero-wolf.com/locator).




### BLOWER OPTIONS

- 300 CFM Internal
- 450 CFM Internal
- 600 CFM Internal
- 900 CFM Internal
- 1200 CFM Internal
- 600 CFM Inline
- 1100 CFM Inline
- 600 CFM Remote
- 900 CFM Remote
- 1200 CFM Remote
- 1500 CFM Remote

**PRODUCT SPECIFICATIONS**

Model	PWC362418
Dimensions	36"W x 18"H x 24"D
Weight	78 lbs
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical
Discharge Dimensions	10" Round
Bottom of Hood to Countertop	30" to 36"

**ELECTRICAL**



**NOTE:** Dimensions in parenthesis are in millimeters unless otherwise specified

**DIMENSIONS**

