

PWC482418

FEATURES

- _____Rigorously tested for decades of use
- _____Exceptional support from our Customer Care team in Madison
- _____Heavy-duty stainless steel construction
- _____Blower required (internal, in-line or remote blowers available)
- _____Bright halogen lighting
- _____Heat sentry for safety
- _____Recessed controls for sleeker look
- _____Transition with backdraft minimizes backward flow of cold air
- _____Infinite speed blower control
- _____Install with accessory duct cover for chimney-style hood
- _____Handfinished with hemmed edges and welded seams

ACCESSORIES

- _____1100 CFM Inline Blower
- _____12" Duct Cover
- _____1200 CFM Internal Blower
- _____1200 CFM Remote Blower
- _____1500 CFM Remote Blower
- _____18" Duct Cover
- _____24" Duct Cover
- _____30" Duct Cover
- _____300 CFM Internal Blower
- _____36" Duct Cover
- _____400 CFM Internal Blower
- _____6" Duct Cover
- _____600 CFM Inline Blower
- _____600 CFM Internal Blower
- _____600 CFM Remote Blower
- _____800 CFM Internal Blower
- _____900 CFM Remote Blower
- _____Backsplash
- _____Backsplash with Warming Racks
- _____Make-Up Air Damper
- _____38" high stainless steel backsplash with or without warming racks

Accessories available through an authorized dealer.
For local dealer information, visit subzero-wolf.com/locator.




BLOWER OPTIONS

- 300 CFM Internal
- 400 CFM Internal
- 600 CFM Internal
- 800 CFM Internal
- 1200 CFM Internal
- 600 CFM Inline
- 1100 CFM Inline
- 600 CFM Remote
- 900 CFM Remote
- 1200 CFM Remote
- 1500 CFM Remote

PRODUCT SPECIFICATIONS

Model	PWC482418
Dimensions	48"W x 18"H x 24"D
Weight	94 lbs
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical
Discharge Dimensions	10" Round
Bottom of Hood to Countertop	30" to 36"

ELECTRICAL



NOTE: Dimensions in parenthesis are in millimeters unless otherwise specified

DIMENSIONS

