

## PWC542418

## FEATURES

- \_\_\_\_\_Rigorously tested for decades of use
- \_\_\_\_\_Exceptional support from our Customer Care team in Madison
- \_\_\_\_\_Heavy-duty stainless steel construction
- \_\_\_\_\_Blower required (internal, in-line or remote blowers available)
- \_\_\_\_\_Bright halogen lighting
- \_\_\_\_\_Heat sentry for safety
- \_\_\_\_\_Recessed controls for sleeker look
- \_\_\_\_\_Transition with backdraft minimizes backward flow of cold air
- \_\_\_\_\_Infinite speed blower control
- \_\_\_\_\_Install with accessory duct cover for chimney-style hood
- \_\_\_\_\_Handfinished with hemmed edges and welded seams

## ACCESSORIES

- \_\_\_\_\_1100 CFM Inline Blower
- \_\_\_\_\_12" Duct Cover
- \_\_\_\_\_1200 CFM Internal Blower
- \_\_\_\_\_1200 CFM Remote Blower
- \_\_\_\_\_1500 CFM Remote Blower
- \_\_\_\_\_18" Duct Cover
- \_\_\_\_\_24" Duct Cover
- \_\_\_\_\_30" Duct Cover
- \_\_\_\_\_300 CFM Internal Blower
- \_\_\_\_\_36" Duct Cover
- \_\_\_\_\_400 CFM Internal Blower
- \_\_\_\_\_6" Duct Cover
- \_\_\_\_\_600 CFM Inline Blower
- \_\_\_\_\_600 CFM Internal Blower
- \_\_\_\_\_600 CFM Remote Blower
- \_\_\_\_\_800 CFM Internal Blower
- \_\_\_\_\_900 CFM Remote Blower
- \_\_\_\_\_Backsplash
- \_\_\_\_\_Backsplash with Warming Racks
- \_\_\_\_\_Make-Up Air Damper
- \_\_\_\_\_38" high stainless steel backsplash with or without warming racks

Accessories available through an authorized dealer.  
For local dealer information, visit [subzero-wolf.com/locator](http://subzero-wolf.com/locator).




## BLOWER OPTIONS

- 300 CFM Internal
- 400 CFM Internal
- 600 CFM Internal
- 800 CFM Internal
- 1200 CFM Internal
- 600 CFM Inline
- 1100 CFM Inline
- 600 CFM Remote
- 900 CFM Remote
- 1200 CFM Remote
- 1500 CFM Remote

**PRODUCT SPECIFICATIONS**

Model	PWC542418
Dimensions	54"W x 18"H x 24"D
Weight	106 lbs
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical
Discharge Dimensions	10" Round
Bottom of Hood to Countertop	30" to 36"

**ELECTRICAL**



**NOTE:** Dimensions in parenthesis are in millimeters unless otherwise specified

**DIMENSIONS**

