

## PW602418

### FEATURES

- \_\_\_\_\_ Rigorously tested for decades of use
- \_\_\_\_\_ Exceptional support from our Customer Care team in Madison
- \_\_\_\_\_ Heavy-duty stainless steel construction
- \_\_\_\_\_ Blower required (internal, in-line or remote blowers available)
- \_\_\_\_\_ Handfinished with hemmed edges and welded seams
- \_\_\_\_\_ Recessed controls for sleeker look
- \_\_\_\_\_ Infinite speed blower control
- \_\_\_\_\_ Heat sentry for safety
- \_\_\_\_\_ Bright halogen lighting
- \_\_\_\_\_ Transition with backdraft minimizes backward flow of cold air

### ACCESSORIES

- \_\_\_\_\_ 1100 CFM Inline Blower
- \_\_\_\_\_ 1200 CFM Internal Blower
- \_\_\_\_\_ 1200 CFM Remote Blower
- \_\_\_\_\_ 1500 CFM Remote Blower
- \_\_\_\_\_ 18" Duct Cover
- \_\_\_\_\_ 36" Duct Cover
- \_\_\_\_\_ 400 CFM Internal Blower
- \_\_\_\_\_ 6" Duct Cover
- \_\_\_\_\_ 800 CFM Internal Blower
- \_\_\_\_\_ Backsplash
- \_\_\_\_\_ Backsplash with Warming Racks
- \_\_\_\_\_ Horizontal Discharge Kit
- \_\_\_\_\_ Make-Up Air Damper

Accessories available through an authorized dealer.  
For local dealer information, visit [subzero-wolf.com/locator](http://subzero-wolf.com/locator).



### BLOWER OPTIONS

- 300 CFM Internal
- 400 CFM Internal
- 600 CFM Internal
- 800 CFM Internal
- 1200 CFM Internal
- 600 CFM Inline
- 1100 CFM Inline
- 600 CFM Remote
- 900 CFM Remote
- 1200 CFM Remote
- 1500 CFM Remote

**PRODUCT SPECIFICATIONS**

Model	PW602418
Dimensions	60"W x 18"H x 24"D
Weight	116 lbs
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical or Horizontal
Discharge Dimensions	10" Round
Bottom of Hood to Countertop	30" to 36"

**ELECTRICAL**



**NOTE:** Dimensions in parenthesis are in millimeters unless otherwise specified

**DIMENSIONS**

